

Application No. 09/575,552

Docket No. 22-0099

**Amendments to the Claims**

1-3 (Cancelled).

4 (Currently Amended): A method for scheduling, in real-time, an order in which data packets from a plurality of uplink channels stored in priority-class queues are organized in a downlink channel of a satellite communications network, the method comprising:

conveying data packets over a downlink channel in an order determined by a packet service schedule;

monitoring at least one traffic parameter associated with at least one data stream stored in a priority-class queue, the traffic parameter being representative of an actual bandwidth usage of the corresponding priority-class queue;

while conveying data packets over the downlink channel, modifying the packet service schedule based on said at least one traffic parameter, and

The method of claim 1, further comprising:

measuring a phase of each data stream stored in a priority-class queue, said phase being indicative of an amount of time lapsed since a data packet from a particular priority-class queue was output to the downlink channel.

5-10 (Cancelled).

11 (Currently Amended): A method for scheduling, in real-time, an order in which data packets from a plurality of uplink channels stored in priority-class queues are organized

Application No. 09/575,552

Docket No. 22-0099

in a downlink channel of a satellite communications network, the method comprising:  
conveying data packets over a downlink channel in an order determined by a  
packet service schedule;

monitoring at least one traffic parameter associated with at least one data stream  
stored in a priority-class queue, the traffic parameter being representative of an actual  
bandwidth usage of the corresponding priority-class queue;

while conveying data packets over the downlink channel, modifying the packet  
service schedule based on said at least one traffic parameter; and

The method of claim 1, further comprising:

adjusting the bandwidth allocated to at least one priority-class queue, while the  
priority-class queue is storing data packets.

12 (Currently Amended): A method for scheduling, in real-time, an order in which data  
packets from a plurality of uplink channels stored in priority-class queues are organized  
in a downlink channel of a satellite communications network, the method comprising:  
conveying data packets over a downlink channel in an order determined by a  
packet service schedule;

monitoring at least one traffic parameter associated with at least one data stream  
stored in a priority-class queue, the traffic parameter being representative of an actual  
bandwidth usage of the corresponding priority-class queue;

while conveying data packets over the downlink channel, modifying the packet  
service schedule based on said at least one traffic parameter; and

The method of claim 1, further comprising:

Application No. 09/575,552

Docket No. 22-0099

modifying the packet service schedule by adjusting an amount of bandwidth allocated to at least one priority-class queue while the priority-class queue is storing data packets.

13 (Original): A communications satellite, comprising:

at least one uplink and downlink for conveying data packets over communications channels;

queues for collecting data packets from uplinks and outputting the data packets to a downlink using a dynamic amount of bandwidth; and

a scheduler for allocating bandwidth to at least one queue, said scheduler changing an amount of bandwidth allocated to at least one queue while said queue is buffering data packets between an uplink and downlink.

14 (Original): The communications satellite of claim 13, further comprising:

a bandwidth measurement module for measuring a statistical bandwidth actually being used by at least one queue, said scheduler updating the bandwidth allocation of said at least one queue based on said measured statistical bandwidth.

15 (Original): The communications satellite of claim 13, further comprising:

a look-up table storing a master frame allocating bandwidth to at least one queue, said master frame comprising a plurality of time slots, each time slot including a priority queue index identifying a queue to output a data packet during the associated time slot.

Application No. 09/575,552

Docket No. 22-0099

16 (Original): The communications satellite of claim 13, further comprising:

means for measuring data packet rate for each queue, said scheduler modifying bandwidth allocation based on the measured data packet rate.

17 (Original): The communications satellite of claim 13, wherein said scheduler further comprises:

a processor calculating statistical bandwidth allocation to said queues based on actual traffic arriving at said queues.

18 (Original): The communications satellite of claim 13, wherein said scheduler further comprises:

memory storing a packet service schedule identifying an order in which data packets pass over the downlink, said packet service schedule being based on bandwidth allocation calculated by said scheduler.

19 (Original): The communications satellite of claim 13, further comprising:

means for monitoring at least one traffic parameter associated with each downlink stream, said traffic parameter being representative of an actual usage of a priority-class associated with a queue, the scheduler changing bandwidth allocation based on said traffic parameter.

20 (Original): The communications satellite of claim 13, further comprising:

a switch for switching data packets from each uplink channel to a unique queue

Application No. 09/575,552

Docket No. 22-0099

based on priority-classes of the data packets.

21 (Original): The communications satellite of claim 13, further comprising:

a processor calculating a new bandwidth allocation based on a Packet Fair Queuing algorithm.